



LUMINAIRE SPECIFICATIONS
 CATALOGUE NO.: K56-S-K24-P4AR-III-75(SSL)
 -7030-120:277-4K-#6
 POLE ADAPTOR: K24
 OPTICAL SYSTEM: FLAT ARRAY ACRYLIC RIPPLED
 IES CLASS: TYPE III
 INPUT WATTAGE: 75W (7030 SERIES)
 (SOLID STATE LIGHTING)
 CCT/DIODE: 400K/HE5
 LANTERN TYPE: TUDOR (WITH SPURS)
 LINE VOLTAGE: 120:277V
 PAINT: BASE COAT: ANODIZED BLACK
 TOP COAT: TEXTURED BLACK
 OPTIONS: #6 FINIAL
 (PR NOT REQUIRED)

DRIVER SPECIFICATIONS
 MANUFACTURER: MEANWELL
 PART NO.: HLG-100H-24B

OPTIONS
 QUICK DISCONNECT

WEATHERPROOF RECEPTACLE (SPLIT WIRED AND PRE-WIRED TO BASE BY MANUFACTURE)

ACRYLIC CANVAS BANNERS 3' X 1'-6" AS MANUFACTURED BY: KALAMAZOO BANNER WORKS, INC., 1-800-525-6424 (OR EQUAL) - MOUNT PERPENDICULAR TO SIDEWALK

STYLE, COLOR AND LETTERING OF BANNERS TO BE SELECTED BY CITY.

BANNER FLEX MOUNTING BRACKET AS MANUFACTURED BY KALAMAZOO BANNER WORKS, INC (OR EQUAL) PAINTED BLACK

POLE
 MODEL: C050
 TOP DIA: 4.4" F-F
 TAPER: .18"/FT
 CONSTRUCTION: CENTRIFUGAL CAST FIBERGLASS COMPOSITE
 TENON: 3.5" OD 3.5" EXPOSED LENGTH 6061-T6 ALUM
 HAND HOLE: 2"x5" @ 14" ABOVE GRADE WITH COVER
 PAINTED TO MATCH POLE
 WIRE ENTRY: (2) 2 1/2" RND @ 24" BELOW GRADE
 PAINT: UV & CHEMICAL RESISTANT
 COLOR: CUSTOM - CUSTOMER TO SPECIFY
 OPTION: RC BLACK
 MAX ATTACHMENT WEIGHT: 100 LBS
 MAX ATTACHMENT EPA: 8.4 @ 140 MPH ANSI
 POLE WEIGHT: 85 LBS APPROX

NOTE: ALL MOUNTING HARDWARE TO BE STAINLESS STEEL



**STANDARD CONSTRUCTION DETAIL
 LED LIGHT FIXTURE & DECORATIVE POLE**

NTS

INDEX

SC-7A

MAY 2020